

# TOWER SERIES



**R410A**  
REFRIGERANT



## AST-24Ai

- Designed with an emphasis on aesthetics
- Usable for larger areas such as offices, meeting rooms, restaurants etc.
- Turbo heating and cooling
- Equipped with horizontal and vertical electric louver
- Self-diagnosis function
- Intelligent defrost system
- WiFi control
- Controlled by built-in or remote controller



**DC INVERTER**

## TECHNICAL PARAMETERS

MODEL			AST-24AI		
Capacity cooling / heating	kW		7,2 / 7,5		
Power supply	Hz / V		1~ / 50 / 220-240		
SEER / SCOP	-		6,1 / 4,0		
Sound pressure level at 1m	ID	dB(A)	49 / 45 / 42 / 39		
	OD	dB(A)	60		
Dimension (w x h x d)/Net weight	ID	mm/kg	507 x 1770 x 320 / 40,0		
	OD	mm/kg	955 x 700 x 396 / 53,5		
Operating temperature range cooling/heating	°C		-15 ~ 48 / -15 ~ 24		

For detailed technical parameters see technical part of catalogue. This catalogue sheet does not apply to project documentation.  
Contains fluorinated greenhouse gases covered by the Kyoto Protocol. R410A (50% HFC-32, 50% HFC-125), GWP of refrigerant used: 2088.