

**Information requirements  
(air-to-air air conditioners)**

| Model(s):ASF-48BI2, ASGE-48BI2                                                                                                                                                                                                                                                                                                                                                                                                            |                                      |       |                                 |                                                                                    |              |       |                       |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|-------|---------------------------------|------------------------------------------------------------------------------------|--------------|-------|-----------------------|
| Outdoor side heat exchanger of air conditioner                                                                                                                                                                                                                                                                                                                                                                                            | air                                  |       |                                 |                                                                                    |              |       |                       |
| Indoor side heat exchanger of air conditioner                                                                                                                                                                                                                                                                                                                                                                                             | air                                  |       |                                 |                                                                                    |              |       |                       |
| Type                                                                                                                                                                                                                                                                                                                                                                                                                                      | compressor driven vapour compression |       |                                 |                                                                                    |              |       |                       |
| If applicable: driver of compressor                                                                                                                                                                                                                                                                                                                                                                                                       | electric motor                       |       |                                 |                                                                                    |              |       |                       |
| Item                                                                                                                                                                                                                                                                                                                                                                                                                                      | Symbol                               | Value | Unit                            | Item                                                                               | Symbol       | Value | Unit                  |
| Rated cooling capacity                                                                                                                                                                                                                                                                                                                                                                                                                    | $P_{rated,c}$                        | 13,4  | kW                              | Seasonal space cooling energy efficiency                                           | $\eta_{s,c}$ | 254,7 | %                     |
| Declared cooling capacity for part load at given outdoor temperatures $T_j$ and indoor 27°/19 °C (dry/wet bulb)                                                                                                                                                                                                                                                                                                                           |                                      |       |                                 | Declared energy efficiency ratio for part load at given outdoor temperatures $T_j$ |              |       |                       |
| $T_j = + 35 \text{ }^\circ\text{C}$                                                                                                                                                                                                                                                                                                                                                                                                       | $P_{dc}$                             | 13,42 | kW                              | $T_j = + 35 \text{ }^\circ\text{C}$                                                | $EER_d$      | 3,08  | -                     |
| $T_j = + 30 \text{ }^\circ\text{C}$                                                                                                                                                                                                                                                                                                                                                                                                       | $P_{dc}$                             | 9,09  | kW                              | $T_j = + 30 \text{ }^\circ\text{C}$                                                | $EER_d$      | 4,50  | -                     |
| $T_j = + 25 \text{ }^\circ\text{C}$                                                                                                                                                                                                                                                                                                                                                                                                       | $P_{dc}$                             | 5,97  | kW                              | $T_j = + 25 \text{ }^\circ\text{C}$                                                | $EER_d$      | 6,80  | -                     |
| $T_j = + 20 \text{ }^\circ\text{C}$                                                                                                                                                                                                                                                                                                                                                                                                       | $P_{dc}$                             | 2,59  | kW                              | $T_j = + 20 \text{ }^\circ\text{C}$                                                | $EER_d$      | 13,76 | -                     |
| Degradation co-efficient for air conditioners(*)                                                                                                                                                                                                                                                                                                                                                                                          | $C_{dc}$                             | 0,25  | —                               |                                                                                    |              |       | -                     |
| Power consumption in modes other than ‘active mode’                                                                                                                                                                                                                                                                                                                                                                                       |                                      |       |                                 |                                                                                    |              |       |                       |
| Off mode                                                                                                                                                                                                                                                                                                                                                                                                                                  | $P_{OFF}$                            | 0,005 | kW                              | Crankcase heater mode                                                              | $P_{CK}$     | 0,000 | kW                    |
| Thermostat-off mode                                                                                                                                                                                                                                                                                                                                                                                                                       | $P_{TO}$                             | 0,005 | kW                              | Standby mode                                                                       | $P_{SB}$     | 0,005 | kW                    |
| Other items                                                                                                                                                                                                                                                                                                                                                                                                                               |                                      |       |                                 |                                                                                    |              |       |                       |
| Capacity control                                                                                                                                                                                                                                                                                                                                                                                                                          | variable                             |       |                                 | For air-to-air air conditioner: air flow rate, outdoor measured                    | —            | 5200  | $\text{m}^3/\text{h}$ |
| Sound power level, indoor/outdoor                                                                                                                                                                                                                                                                                                                                                                                                         | $L_{WA}$                             | 67/73 | dB                              |                                                                                    |              |       |                       |
| If engine driven: Emissions of nitrogen oxides                                                                                                                                                                                                                                                                                                                                                                                            | $\text{NO}_x(**)$                    | -     | mg/kWh fuel input GCV           |                                                                                    |              |       |                       |
| GWP of the refrigerant                                                                                                                                                                                                                                                                                                                                                                                                                    | 675                                  |       | kg $\text{CO}_2$ eq (100 years) |                                                                                    |              |       |                       |
| Contact details:<br>West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070                                                                                                                                                                                                                                                                                                                                                             |                                      |       |                                 | Name of manufacturer:<br>GREE ELECTRIC APPLIANCES,INC. OF ZHUHAI                   |              |       |                       |
| <p>(*) If <math>C_{dc}</math> is not determined by measurement then the default degradation coefficient air conditioners shall be 0,25.<br/> (**) From 26 September 2018.<br/> Where information relates to multi-split air conditioners, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.</p> |                                      |       |                                 |                                                                                    |              |       |                       |

**Information requirements  
(heat pump)**

|                                                                                                                                                                                                                                                                                                                                                                                                                     |                           |       |                                   |                                                                                       |              |        |         |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|-------|-----------------------------------|---------------------------------------------------------------------------------------|--------------|--------|---------|
| Model(s):GUD140ZD1/A-S , GUD140W1/NhA-S                                                                                                                                                                                                                                                                                                                                                                             |                           |       |                                   |                                                                                       |              |        |         |
| Outdoor side heat exchanger of heat pump                                                                                                                                                                                                                                                                                                                                                                            | air                       |       |                                   |                                                                                       |              |        |         |
| Indoor side heat exchanger of heat pump                                                                                                                                                                                                                                                                                                                                                                             | air                       |       |                                   |                                                                                       |              |        |         |
| Indication if the heater is equipped with a supplementary heater                                                                                                                                                                                                                                                                                                                                                    | no                        |       |                                   |                                                                                       |              |        |         |
| If applicable: driver of compressor                                                                                                                                                                                                                                                                                                                                                                                 | electric motor            |       |                                   |                                                                                       |              |        |         |
| Parameters declared for                                                                                                                                                                                                                                                                                                                                                                                             | Average climate condition |       |                                   |                                                                                       |              |        |         |
| Item                                                                                                                                                                                                                                                                                                                                                                                                                | symbol                    | value | unit                              | Item                                                                                  | symbol       | value  | unit    |
| Rated heating capacity                                                                                                                                                                                                                                                                                                                                                                                              | $P_{rated,h}$             | 15,5  | kW                                | Seasonal space heating energy efficiency                                              | $\eta_{s,h}$ | 163,2  | %       |
| Declared heating capacity for part load at indoor temperature 20 °C and outdoor temperature $T_j$                                                                                                                                                                                                                                                                                                                   |                           |       |                                   | Declared coefficient of performance for part load at given outdoor temperatures $T_j$ |              |        |         |
| $T_j = -7\text{ °C}$                                                                                                                                                                                                                                                                                                                                                                                                | $P_{dh}$                  | 8,71  | kW                                | $T_j = -7\text{ °C}$                                                                  | $COP_d$      | 2,64   | -       |
| $T_j = +2\text{ °C}$                                                                                                                                                                                                                                                                                                                                                                                                | $P_{dh}$                  | 5,39  | kW                                | $T_j = +2\text{ °C}$                                                                  | $COP_d$      | 4,01   | -       |
| $T_j = +7\text{ °C}$                                                                                                                                                                                                                                                                                                                                                                                                | $P_{dh}$                  | 3,34  | kW                                | $T_j = +7\text{ °C}$                                                                  | $COP_d$      | 5,67   | -       |
| $T_j = +12\text{ °C}$                                                                                                                                                                                                                                                                                                                                                                                               | $P_{dh}$                  | 1,64  | kW                                | $T_j = +12\text{ °C}$                                                                 | $COP_d$      | 5,67   | -       |
| $T_{biv}$ = bivalent temperature                                                                                                                                                                                                                                                                                                                                                                                    | $P_{dh}$                  | 8,71  | kW                                | $T_{biv}$ = bivalent temperature                                                      | $COP_d$      | 2,64   | -       |
| $T_{OL}$ = operation limit                                                                                                                                                                                                                                                                                                                                                                                          | $P_{dh}$                  | 9,83  | kW                                | $T_{OL}$ = operation limit                                                            | $COP_d$      | 2,32   | -       |
| $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$ )                                                                                                                                                                                                                                                                                                                                                                   | $P_{dh}$                  | NA    | kW                                | $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$ )                                     | $COP_d$      | NA     | -       |
| Bivalent temperature                                                                                                                                                                                                                                                                                                                                                                                                | $T_{biv}$                 | -7.00 | °C                                | Operation limit temperature                                                           | $T_{ol}$     | -10.00 | °C      |
| Degradation co-efficient heat pumps(**)                                                                                                                                                                                                                                                                                                                                                                             | $C_{dh}$                  | 0,25  | —                                 |                                                                                       |              |        |         |
| Power consumption in modes other than 'active mode'                                                                                                                                                                                                                                                                                                                                                                 |                           |       |                                   | Supplementary heater                                                                  |              |        |         |
| Off mode                                                                                                                                                                                                                                                                                                                                                                                                            | $P_{OFF}$                 | 0,005 | kW                                | Back-up heating capacity (*)                                                          | $e_{lbu}$    | 0,169  | kW      |
| Thermostat-off mode                                                                                                                                                                                                                                                                                                                                                                                                 | $P_{TO}$                  | 0,015 | kW                                | Type of energy input                                                                  | Electric     |        |         |
| Crankcase heater mode                                                                                                                                                                                                                                                                                                                                                                                               | $P_{CK}$                  | 0,000 | kW                                | Standby mode                                                                          | $P_{SB}$     | 0,005  | kW      |
| Other items                                                                                                                                                                                                                                                                                                                                                                                                         |                           |       |                                   |                                                                                       |              |        |         |
| Capacity control                                                                                                                                                                                                                                                                                                                                                                                                    | variable                  |       |                                   | air flow rate, outdoor measured                                                       | —            | 5200   | $m^3/h$ |
| Sound power level, indoor/outdoor measured                                                                                                                                                                                                                                                                                                                                                                          | $L_{WA}$                  | 66/72 | dB                                |                                                                                       |              |        |         |
| Emissions of nitrogen oxides (if applicable)                                                                                                                                                                                                                                                                                                                                                                        | $NO_x(***)$               | -     | mg/kWh input GCV                  | Rated brine or water flow rate, outdoor side heat exchanger                           | —            | -      | $m^3/h$ |
| GWP of the refrigerant                                                                                                                                                                                                                                                                                                                                                                                              | 675                       |       | kg CO <sub>2</sub> eq (100 years) |                                                                                       |              |        |         |
| Contact details:<br>West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070                                                                                                                                                                                                                                                                                                                                       |                           |       |                                   | Name of manufacturer:<br>GREE ELECTRIC APPLIANCES,INC. OF ZHUHAI                      |              |        |         |
| (*)<br>(**) If $C_{dh}$ is not determined by measurement then the default degradation coefficient of heat pumps shall be 0,25.<br>(***) From 26 September 2018.<br>Where information relates to multi-split heat pumps, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer. |                           |       |                                   |                                                                                       |              |        |         |