

KONZOLNA SERIJA



R410A
REFRIGERANT



ASP-09AI
ASP-12AI
ASP-18AI

- Energetski razred A++/A+
- Odvod kondenzata na obje strane
- 7 brzina ventilatora
- Dvostruki izlaz zraka za grijanje



PLASMA+TEC DC INVERTER

STANDARDNA OPREMA

- WIFI modul
- Standardni filteri - katehinski filter SAF-OPWC4
- i srebrni filter SAF-OPWS4
- Hladna plazma generator
- "Dry on/off" kontakt
- Grijani kompresor i kućište vanjske jedinice



MODEL			ASP-09AI	ASP-12AI	ASP-18AI	
Kapacitet hlađenje / grijanje	kW		2,7 / 2,8	3,5 / 3,8	5,2 / 5,3	
Napajanje jedinice	Hz / V		1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	
SEER / SCOP	-		6,5 / 4,0	6,4 / 4,0	6,5 / 4,1	
Energetski razred (A, W, C)	-		A++ / A+	A++ / A+	A++ / A+	
Razina buke	UJ	dB(A)	40 / 36 / 34 / 32 / 30 / 26 / 23	42 / 40 / 38 / 36 / 34 / 31 / 25	47 / 45 / 42 / 40 / 37 / 35 / 31	
	VJ	dB(A)	52	52	57	
Dimenzije (Š x V x D)	UJ	mm/kg	700 x 215 x 600 / 15,5	700 x 215 x 600 / 15,5	700 x 215 x 600 / 15,5	
	VJ	mm/kg	776 x 540 x 320 / 31,0	776 x 540 x 320 / 31,5	955 x 700 x 396 / 46,0	
Raspon radne temperature hlađenje/grijanje	°C		-15-43 / -22-24	-15-43 / -22-24	-15-43 / -22-24	

Za detaljnu tehničku specifikaciju proizvoda, molimo pogledajte tehnički dio kataloga. Ova podatkovna tablica ne služi kao osnova za obradu projektnih dokumenata.

Sadrži fluorirane stakleničke plinove obuhvaćene Kyotskim protokolom.

Rashladno sredstvo: R410A (50 % HFC-32, 50 % HFC-125) s GWP (Potencijal globalnog zagrijavanja) 2088.

DODATNA OPREMA

- Zdravi filteri
- GSM modul G2S
- Žičani upravljač SWC-02
- Centralni upravljač SCC-16